



GRAPHITE DRY LUBRICANT

SAFETY DATA SHEET

According to Canada's Hazardous Products Regulations (HPR) SOR/2015-17

SECTION 1: PRODUCT AND COMPANY IDENTIFICATION

Product identifier

Chemical Name	Mixture
CAS No.	Mixture
Trade Name	GRAPHITE DRY LUBRICANT
Product Code	10-501139

Relevant identified uses of the substance or mixture and uses advised against

Identified Use(s)	PC24 Lubricants, greases, release products
Uses Advised Against	None
Company Identification	The Blaster Corporation 8500 Sweet Valley Drive Valley View, Ohio 44125 USA www.blastercorp.com
Telephone	(800) 858-6605
Fax	(216) 901-5801

Emergency telephone number

Emergency Phone No.

Transportation Emergency: CHEMTEL 800-255-3924

SECTION 2: HAZARDS IDENTIFICATION

Classification of the substance or mixture

HPR/WHIMIS 2015/GHS Classification

Flam. Aerosol 1; Liquefied gas; Skin Irrit. 2; Eye Irrit. 2; STOT SE 3; Asp. Tox. 1

Label elements

Hazard Symbol



Signal Word(s)

DANGER

Hazard Statement(s)

Extremely flammable aerosol.
Contains gas under pressure; may explode if heated.
Causes skin irritation.
Causes serious eye irritation.
May be fatal if swallowed and enters airways.
May cause drowsiness or dizziness.

Precautionary Statement(s)

Keep away from heat/sparks/open flames/hot surfaces. – No smoking.
Do not spray on an open flame or other ignition source.
Do not pierce or burn, even after use.



GRAPHITE DRY LUBRICANT

Use only outdoors or in a well-ventilated area.

Avoid breathing spray.

Protect from sunlight and do not expose to temperatures exceeding 50 °C/122 °F.

Wear protective gloves/eye protection.

Wash hands and exposed skin after use.

Keep out of reach of children.

Toxic to aquatic life. Harmful to aquatic life with long lasting effects.

Other hazards

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

Hazardous Ingredient(s)	% wt. *	CAS No.	Hazard classification
Petroleum Distillate	30 - 40	Trade Secret	Flam. Liq. 2; H225 Asp. Tox. 1; H304 Skin Irrit. 2; H315 STOT SE 3; H336 Aquatic Acute 2; H401 Aquatic Chronic 3; H412
Isopropanol	30 - 35	67-63-0	Flam. Liq. 2; H225 Eye Irrit. 2; H319 STOT SE 3; H336
Propane	15 - 20	74-98-6	Flam. Gas 1; H220 Liquefied gas; H280
Butane	10 - 15	106-97-8	Flam. Gas 1; H220 Liquefied gas; H280

Additional Information - None

* The exact percentage withheld as a trade secret in accordance with 29 CFR 1910.1200.

SECTION 4: FIRST AID MEASURES



Description of first aid measures

Inhalation

IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. If breathing is laboured, administer oxygen. Call a POISON CENTER/doctor if you feel unwell.

Skin Contact

Wash affected skin with soap and water. If skin irritation occurs, get medical advice/attention. Take off contaminated clothing and wash it before reuse.

Eye Contact

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists, get medical advice/attention.

Ingestion

Do not give anything by mouth to an unconscious person. Seek medical treatment. Do NOT induce vomiting.

Most important symptoms and effects, both acute and delayed

Aspiration of droplets may cause pulmonary oedema. May cause drowsiness and dizziness.

Indication of any immediate medical attention and special treatment needed

IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.



GRAPHITE DRY LUBRICANT

SECTION 5: FIRE-FIGHTING MEASURES

Extinguishing Media

- Suitable Extinguishing Media
- Unsuitable Extinguishing Media

Extinguish with carbon dioxide, dry chemical, foam or water spray. Do not use water jet.

Special hazards arising from the substance or mixture

Highly flammable vapour (flash point below 23°C).

Advice for fire-fighters

A self contained breathing apparatus and suitable protective clothing should be worn in fire conditions. Keep containers cool by spraying with water if exposed to fire.

SECTION 6: ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Keep away from heat/sparks/open flames/hot surfaces. – No smoking. Take precautionary measures against static discharges. Avoid contact with skin and eyes. Avoid breathing vapours.

Environmental precautions

Prevent liquid entering sewers, basements and workpits. Collect spillage.

Methods and material for containment and cleaning up

Cover spills with inert absorbent material. Transfer to a container for disposal or recovery.

Reference to other sections

None

Additional Information

None

SECTION 7: HANDLING AND STORAGE

Precautions for safe handling

Keep away from heat/sparks/open flames/hot surfaces. – No smoking. Avoid contact with skin and eyes. Use product in a well-ventilated area only.

Conditions for safe storage, including any incompatibilities

- Storage temperature

Store locked up. Keep in a cool, well ventilated place. Protect from sunlight. Store at temperatures not exceeding 50°C/ 120°F. Keep container tightly closed.

- Incompatible materials

This product should be stored away from sources of strong heat or oxidising chemicals.

Specific end use(s)

PC24 Lubricants, greases, release products

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

Occupational Exposure Limits

SUBSTANCE.	CAS No.	(8hr TWA)		(STEL)		Note:
		OEL (Canada)	TLV (ACGIH)	PEL (Canada)	TLV (ACGIH)	
Heptane, branched, cyclic, and linear	426260-76-6	400 ppm*	1500 mg/m ³	500 ppm*	-----	*n-heptane
Isopropanol	67-63-0	200 ppm	200 ppm	400 ppm	400 ppm	-----
n-Butanol	71-36-3	20 ppm	20 ppm	-----	-----	-----
Propylene glycol methyl ester	107-98-2	100 ppm	50 ppm	150 ppm	100 ppm	-----
n-Butane	106-97-8	800 ppm	250 ppm	-----	-----	-----
Propane	74-98-6	1000 ppm	Aspyx.#	-----	-----	#

*Assure minimum oxygen content of work atmosphere.

Recommended monitoring method

NIOSH 1550 (Naphthas); NIOSH 1500 (hydrocarbons, B.P. 36 - 126 °C); NIOSH 1400 (alcohols I); NIOSH 1401 (alcohols II); NIOSH 2554



GRAPHITE DRY LUBRICANT

(Glycol Ethers)

Exposure controls

Appropriate engineering controls

Provide adequate ventilation to ensure that the occupational exposure limit is not exceeded.

Personal protection equipment

Eye/face protection



Wear protective eyewear (goggles, face shield, or safety glasses).

Skin protection (Hand protection/ Other)



Wear suitable gloves if prolonged skin contact is likely (Butyl rubber)

Respiratory protection



Normally no personal respiratory protection is necessary. In case of insufficient ventilation, wear suitable respiratory equipment.

Thermal hazards

Not normally required. Use gloves with insulation for thermal protection, when needed.

Environmental Exposure Controls

None known

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Appearance	Aerosol spray
Color.	Colorless
Odour	Mild isopropanol odor
Odour Threshold (ppm)	Not available
pH (Value)	Not available
Melting Point (°C) / Freezing Point (°C)	Not available
Boiling point/boiling range (°C):	Not available
Flash Point (°C)	-104 (Propane)
Evaporation Rate	Not available
Flammability (solid, gas)	Extremely flammable
Explosive Limit Ranges	2.1% - 9.5% v/v (Propane)
Vapour pressure (Pascal)	ca. 95×10^4 (Propane)
Vapour Density (Air=1)	ca. 1.56 @ 0°C (Propane)
Density (g/ml)	Not available
Solubility (Water)	Not available
Solubility (Other)	Not available
Partition Coefficient (n-Octanol/water)	Not available
Auto Ignition Point (°C)	450 (Propane)
Decomposition Temperature (°C)	Not available
Kinematic Viscosity (@37.8°C)	0.83 mm ² /s (Heptane, branched, cyclic, and linear)
Explosive properties	Not explosive.
Oxidising properties	Not oxidising.
Other information	Not available

SECTION 10: STABILITY AND REACTIVITY

Reactivity	Stable under normal conditions.
Chemical stability	Stable.
Possibility of hazardous reactions	None anticipated.



GRAPHITE DRY LUBRICANT

Conditions to avoid

Avoid contact with heat and ignition sources.

Incompatible materials

Strong oxidising agents; Reducing agents; Strong Acids; Aldehydes; Halogens; Amines; Halogenated Hydrocarbons, Alkalis. Do not use with aluminum equipment at temperatures exceeding 120°F.

Hazardous decomposition product(s)

Carbon monoxide, Carbon dioxide, Acrid smoke

SECTION 11: TOXICOLOGICAL INFORMATION

Exposure routes: Inhalation, Skin Contact, Eye Contact

Information on toxicological effects

Heptane, branched, cyclic and linear (CAS# 426260-76-6) - By analogy with similar materials:

Acute toxicity (calculated / estimated)

Oral: LD50 >5 g/kg-bw
Dermal: LD50 >2 g/kg-bw
Inhalation: LC50 = 65 - 103 mg/L (Vapour), 4-hr. rat
May cause drowsiness or dizziness.
May be fatal if swallowed and enters airways.

Irritation/Corrosivity

Causes skin irritation. Repeated exposure may cause skin dryness or cracking. May cause eye irritation.

Sensitisation

It is not a skin sensitizer.

Repeated dose toxicity

NOAEC: 12350 mg/m3 (2 yr, inhal., rat, Systemic effects)
LOAEC: 1650 mg/m3 (2 hr, inhal., rat, CNS effects)
May cause drowsiness or dizziness.

Carcinogenicity

No data. It is unlikely to present a carcinogenic hazard to man.

NTP	IARC	ACGIH	OSHA	NIOSH
No.	No.	No.	No.	No.

Mutagenicity

There is no evidence of mutagenic potential.

Reproductive toxicity

No information available

Isopropanol (CAS# 67-63-0):

Acute toxicity

Oral: LD50 = 5.84 g/kg (rat)
Inhalation: LC50 > 1000 ppm (rat) 6 hour(s)
Dermal: LD50 = 16.4 ml/kg (rabbit) 24 hour(s)
May cause drowsiness or dizziness.

Irritation/Corrosivity

Irritating to eyes.

Sensitisation

It is not a skin sensitizer.

Repeated dose toxicity

NOAEL = 5,000 ppm (Inhalation)
May cause drowsiness or dizziness.

Carcinogenicity

It is unlikely to present a carcinogenic hazard to man.

NTP	IARC	ACGIH	OSHA	NIOSH
No.	No.	No.	No.	No.

Mutagenicity

There is no evidence of mutagenic potential.

Reproductive toxicity

Not available

SECTION 12: ECOLOGICAL INFORMATION

Ecotoxicity

Heptane, branched, cyclic and linear (CAS# 426260-76-6) - By analogy with similar materials:

Short term

LL50 (96 hour): >13.4 mg/L (*Oncorhynchus mykiss*)
EL50 (48 hour): 3 mg/l (*Daphnia magna*, mobility)
EC50 (96 hour): 13 mg/l (*Pseudokirchnerella subcapitata*)



GRAPHITE DRY LUBRICANT

Long Term	NOELR (28 days) 1.5 mg/l (<i>Fish</i>) QSAR LOEC (21 days): 0.32 mg/l (<i>Daphnia magna</i>) NOEL (96 hour) 6.3 mg/l (Algae)
<u>Isopropanol (CAS# 67-63-0):</u>	
Short term	LC50 (96 hour): 10,000 mg/l (Fathead minnow (<i>Pimephales promelas</i>)) LC50 24hour(s): >10,000 mg/l (<i>Daphnia magna</i>)
Long Term	NOEC: 3.37 µmol/l (<i>Daphnia magna</i>) (Growth rate)
Persistence and degradability	Readily biodegradable.
Bioaccumulative potential	Not available.
Mobility in soil	Not available.
Results of PBT and vPvB assessment	Not classified as PBT or vPvB.
Other adverse effects	None known.

SECTION 13: DISPOSAL CONSIDERATIONS

Waste treatment methods	Disposal should be in accordance with local, state or national legislation. Consult an accredited waste disposal contractor or the local authority for advice.
--------------------------------	--

SECTION 14: TRANSPORT INFORMATION

	Land transport (TDG)	Sea transport (IMDG)	Air transport (ICAO/IATA)
UN number	1950	1950	1950
Proper Shipping Name	Aerosols, flammable	Aerosols, flammable	Aerosols, flammable
Transport hazard class(es)	2.1	2.1	2.1
Packing group	Not applicable	Not applicable	Not applicable
Environmental hazards	None assigned	None assigned	None assigned
Special precautions for user	None assigned	None assigned	None assigned

Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code: Not applicable

SECTION 15: REGULATORY INFORMATION

Safety, health and environmental regulations/legislation specific for the substance or mixture:

This product has been classified in accordance to CPR Section 12 and the MSDS contains all the information required by the CPR.

Canada (DSL/NDSL) - All chemicals listed.

SECTION 16: OTHER INFORMATION

The following sections contain revisions or new statements: 1-16.

Date of preparation: November 10, 2016

Hazard Statement(s) and Risk Phrases Listed in: SECTION 2:/ SECTION 3:

Hazard Statement(s)

- H220: Extremely flammable gas.
- H222: Extremely flammable aerosol.
- H225: Highly flammable liquid and vapour.
- H226: Flammable liquid and vapour.
- H280: Contains gas under pressure; may explode if heated.
- H302: Harmful if swallowed.



GRAPHITE DRY LUBRICANT

- H304: May be fatal if swallowed and enters airways.
- H315: Causes skin irritation.
- H318: Causes serious eye damage.
- H319: Causes serious eye irritation.
- H335: May cause respiratory irritation.
- H336: May cause drowsiness or dizziness.
- H401: Toxic to aquatic life.
- H412: Harmful to aquatic life with long lasting effects.

Training advice: None.

Disclaimer: We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind. The information contained in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. It is the user's responsibility to satisfy oneself as to the suitability and completeness of this information for the user's own particular use.